CORCORAN WINDOW FURNISHINGS

Roman Blinds — Chain Operated

The instructions for use shall be read before operating the product.


1 INSTALLATION TYPE

Outside Recess


Fitting outside the window recess? Keep the blind evenly placed either side of the window, and follow the Face Fix instructions.

Inside Recess

Fitting inside the recess? Choose Face Fix, Top Fix, or Side Fix – to the head or side of the recess as appropriate.



Outside Recess




Inside Recess


2 STEP 2: (A)

Top Fix: measure handle protrusion (A), position the bracket, mark holes (B), and screw to the recess.

Face Fix: position with swing arm facing you, mark holes (B), and screw in place.




Bracket layout



Face Fix, swing arm

2 STEP 2: (B)


Push the swing arm anticlockwise as far as it will go. Clip the blind over the bracket, easing the headrail into place, then push clockwise to lock. To release, reverse the process.




3 STEP 3: (A)

Top Fix: measure handle protrusion (A), mark hole (B), and screw to the recess. One fixing point only.


Face Fix: position with the front facing you, mark holes (B), and screw in place.






3 STEP 3: (B)

Angle the headrail into the bracket against the spring, then turn it straight to click into the back. To release, push toward the wall, then tilt down to clear the catches.



Step 1 Step 2

4 FITTING D-RINGS & BREAKAWAY CONNECTORS



Do not tie knots in the lift cord – if the blind is heavy, add extra spools to spread the weight instead.

Rows 1 to N−2: fit a standard D-ring.

Bottom 2 rows only: fit a safety breakaway connector in place of a D-ring.

Safety breakaway connectors must be used on the bottom two rows to comply with child-safety regulations.

SAFETY INSTRUCTIONS

A safety standard for blinds is in place since 1 March 2014, aimed at eliminating strangulation hazards to young children. (Ref: I.S. EN13120 – see www.standards.ie.) Make sure the installer follows this guidance.


- Blinds should be installed at least 1.5m from the floor.
- Fit the tension device as far as possible from the control mechanism to prevent slack cords/chains.
- With a continuous chain, the tension device must still sit no less than 1.5m from the floor.
- Unsure of anything? Call 00353 44 9371038 or email sales@cwf.ie.

NOTE: children can strangle if a safety device isn't installed. Always keep cords and chains out of reach.

5 TENSION DEVICE

Once the headrail and chain length are compliant, fit the safety device securely (Ref: 3909):

1. Set cord length to 1.5m / 59" above the floor and pull through the device.
2. Pull the device down until reasonably taut – not twisted or over-tight.
3. Screw securely to the window frame or wall.
4. Repeat for every cord.



BREAKAWAY SYSTEM

If a continuous chain isn't practical, use a breakaway system instead (Ref: 3021) – no fixed tension device is required.

Fit two easy-break connectors per chain, 200mm apart, the first about 3" / 7cm down from the chain control at the back of the blind (fully raised).

Keep the chain end at least 60cm from the floor.





WARNING

- Young children can be strangled by loops in pull cords, chains, tapes, and inner cords.
- Keep cords out of children's reach – they may become wrapped around a child's neck.
- Move beds, cots, and furniture away from window coverings. Never tie or knot cords together.



The information above is only intended to give general and preliminary guidance to the reader on the General Product Safety Regulations. A full copy of these is available at www.standards.ie. The information should not form the basis upon which the reader makes any decisions or conclusions concerning their own rights or their obligations under the General Product Safety Regulations. CWF Ltd strongly recommend that the reader obtains detailed and specific advice from their own legal counsel concerning their position. CWF Ltd cannot guarantee that the standards or regulations will not be changed before coming into force, or after having come into force will be subject to change, or how the regulations will be interpreted. CWF Ltd are not responsible for any errors, omissions, or statements made. CWF Ltd are not responsible for any loss, howsoever caused, and whether arising directly or indirectly from reliance upon the information and any recommendations provided by Corcoran Window Furnishings to any reader of this material.